

TenarisHydril Wedge 625® TenarisHydril Wedge 625® Dopeless® Blanking Dimensions

DESIGNATION					PIN & BOX		PIN				BOX			
DIAMETER	WALL THICKNESS	WEIGHT	PRODUCT	DRIFT	ADD. LENGTH 1 RECUT	MINIMUM LENGTH	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max	INSIDE DIAMETER min	INSIDE DIAMETER max	OUTSIDE DIAMETER min	OUTSIDE DIAMETER max
in.	in.	lb/ft	---	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)	inch (mm)
4.500	0.290	13.50	TSH WEDGE 625®	3.795" (96.39 mm)	1.400" (36.00 mm)	5.947" (151.05 mm)	4.500" (114.30 mm)	4.545" (115.44 mm)	3.839" (97.51 mm)	3.859" (98.02 mm)	3.910" (99.31 mm)	3.930" (99.82 mm)	4.704" (119.48 mm)	4.724" (119.99 mm)
4.500	0.337	15.10	TSH WEDGE 625®	3.701" (94.01 mm)	1.500" (38.50 mm)	6.376" (161.95 mm)	4.500" (114.30 mm)	4.545" (115.44 mm)	3.745" (95.12 mm)	3.765" (95.63 mm)	3.816" (96.93 mm)	3.836" (97.43 mm)	4.714" (119.74 mm)	4.734" (120.24 mm)
5.000	0.362	18.00	TSH WEDGE 625®	4.151" (105.44 mm)	1.400" (36.00 mm)	6.427" (163.25 mm)	5.000" (127.00 mm)	5.050" (128.27 mm)	4.196" (106.58 mm)	4.216" (107.09 mm)	4.266" (108.36 mm)	4.286" (108.86 mm)	5.232" (132.89 mm)	5.252" (133.40 mm)
5.000	0.408	20.30	TSH WEDGE 625®	4.059" (103.10 mm)	1.300" (33.50 mm)	6.427" (163.25 mm)	5.000" (127.00 mm)	5.050" (128.27 mm)	4.104" (104.24 mm)	4.124" (104.75 mm)	4.174" (106.02 mm)	4.194" (106.53 mm)	5.245" (133.22 mm)	5.265" (133.73 mm)
5.000	0.422	20.80	TSH WEDGE 625®	4.031" (102.39 mm)	1.300" (33.50 mm)	6.427" (163.25 mm)	5.000" (127.00 mm)	5.050" (128.27 mm)	4.076" (103.53 mm)	4.096" (104.04 mm)	4.146" (105.31 mm)	4.166" (105.82 mm)	5.245" (133.22 mm)	5.265" (133.73 mm)
5.000	0.437	21.40	TSH WEDGE 625®	4.001" (101.63 mm)	1.400" (36.00 mm)	6.719" (170.66 mm)	5.000" (127.00 mm)	5.050" (128.27 mm)	4.046" (102.77 mm)	4.066" (103.28 mm)	4.116" (104.55 mm)	4.136" (105.05 mm)	5.246" (133.25 mm)	5.266" (133.76 mm)
5.000	0.478	23.20	TSH WEDGE 625®	3.919" (99.54 mm)	1.500" (38.50 mm)	7.048" (179.02 mm)	5.000" (127.00 mm)	5.050" (128.27 mm)	3.964" (100.69 mm)	3.984" (101.19 mm)	4.034" (102.46 mm)	4.054" (102.97 mm)	5.266" (133.76 mm)	5.286" (134.26 mm)
5.500	0.361	20.00	TSH WEDGE 625®	4.545" (115.44 mm)	1.400" (36.00 mm)	6.408" (162.76 mm)	5.500" (139.70 mm)	5.555" (141.10 mm)	4.699" (119.35 mm)	4.719" (119.86 mm)	4.768" (121.11 mm)	4.788" (121.62 mm)	5.729" (145.52 mm)	5.749" (146.02 mm)
5.500	0.415	23.00	TSH WEDGE 625®	4.653" (118.19 mm)	1.400" (36.00 mm)	6.809" (172.95 mm)	5.500" (139.70 mm)	5.555" (141.10 mm)	4.591" (116.61 mm)	4.611" (117.12 mm)	4.660" (118.36 mm)	4.680" (118.87 mm)	5.756" (146.20 mm)	5.776" (146.71 mm)
5.500	0.476	26.00	TSH WEDGE 625®	4.423" (112.34 mm)	1.500" (38.50 mm)	7.062" (179.37 mm)	5.500" (139.70 mm)	5.555" (141.10 mm)	4.469" (113.51 mm)	4.489" (114.02 mm)	4.538" (115.27 mm)	4.558" (115.77 mm)	5.778" (146.76 mm)	5.798" (147.27 mm)

When this minimum material is supplied, the blank OD and the blank ID must be true to each other within 0.010" TIR (Total Indicator Reading).

na: Not Applicable.

Blank spaces indicate product not currently available.

Dopeless® refers to all Dopeless® versions available for this connection

Contact Tenaris Manufacturing Services at licensees@oilfield.tenaris.com for details.

These Blanking Dimensions are NOT applicable For Handling & lifting plug, HydroTest Caps & HydroTest Plugs.

Yellow - Shaded corresponds to modified from previous document revision.